


LP1-3.5KW

Standard Features

- Kubota Diesel Engine
- Heavy duty syncro-cogged timing belt drive system
- Horizontal water cooled 4-cycle diesel engine
- 4-Point isolation mounts S/S
- Slower 2,800 RPM operating speed for reduced noise and vibration
- Safety shutdown system for high coolant temperature or low lube oil pressure
- Single circuit control system with no printed circuit boards or relays
- Freshwater heat exchanger cooling system
- Cast bronze heat exchanger tank with removable end caps
- Zinc anode in heat exchanger
- Belt-driven impellar type raw water pump
- Stainless Steel water cooled exhaust riser
- 12-Volt electric fuel pump
- Remote 12-Volt electric key switch with Preheat, Start, Run and Stop positions
- Forged brass oil drain valve with safety lock
- Air intake cleaner / silencer
- USCG approved fuel lines
- Awl-Craft 2000 urethane finish
- Circuit breaker - main line
- 5-Year Limited Warranty



Specifications

Kubota Model	EA300NB
Compression Ratio	23 to 1
Cylinders	1
Cu. In. Displacement	19.0
SAE net Intermittent	7/2800 (HP/RPM)
Bore x Stroke	2.95 x 2.76 (in.)
Dims (LxWxH)	28 x 16 x 16.25 (in.)
Enclosure Dims (LxWxH)	31.5 x 20 x 18.5 (in.)
Weight (lbs.)	185
Output (volts)	120/240
Output (amps)	30/15
Output (watts)	3,500
Exhaust Dia.	1.5 in.
Raw water Dia.	5/8 in.
Fuel Line Dia.	5/16 in.
Return Line Dia.	3/16 in.

Specifications are subject to change without notice

Optional Equipment

- Stainless Steel Drip Pan
- Sound Insulation Blanket
- Powder Coated Aluminum Sound Enclosure
- Spare Parts Kit



2880 Hammondville Road • Pompano Beach, FL 33069

Ph: 954-979-5899 • Fax: 954-979-4349

info@phasormarine.com • www.phasormarine.com

rev112323